



### ◆ 尺寸 / Dimension

單位 / Unit : mm

Catalog Number 型號	D	I	L	G	M	d1xd2 標準孔徑 公差 (H8)		Mass** 質量 (g)
						Min	Max	
<b>SMT-16</b>	16	4	23	2.5	M3	4	8	10
<b>SMT-16S</b>	16	4	16	2.5	M3	4	8	8
<b>SMT-19</b>	19	6.5	23	3	M3	6	8	13
<b>SMT-19S</b>	19	4.5	19	3	M3	6	8	11
<b>SMT-20</b>	20	8	26	3	M4	6	10	13
<b>SMT-25</b>	25	10	31	4	M4	6	12	31
<b>SMT-25S</b>	25	7	25	4	M4	6	12	29

### ◆ 性能 / Function

Catalog Number 型號	Rated Torque 一般扭力 (N.m)	Max. Torque 最大扭力 (N.m)	Max. Rotational Frequency 最高回轉數 (min <sup>-1</sup> )	Errors of Shaft End-Play 容許軸向位差 (mm)	Errors of Eccentricity 容許偏心 (mm)	Errors of Angularity 容許偏角 (°)
<b>SMT-16</b>	0.5	1	25000	±0.25	0.25	5
<b>SMT-16S</b>	0.5	1	25000	±0.25	0.25	5
<b>SMT-19</b>	1	2	25000	±0.25	0.25	5
<b>SMT-19S</b>	1	2	25000	±0.25	0.25	5
<b>SMT-20</b>	1.1	2.2	25000	±0.25	0.25	5
<b>SMT-25</b>	1.6	3.2	25000	±0.25	0.25	5
<b>SMT-25S</b>	1.6	3.2	25000	±0.25	0.25	5

### ◆ 材質 / Material: 鋁合金 / Aluminum alloy

### ◆ 特性 / Features

1. 一體成型 / One-body shape.
2. 零背隙 / Zero backlash.
3. 螺旋式溝槽，可撓性特佳 / The grooves are shaped spirally with its excellent flexibility.
4. 最適合 ENCODER / It fits to ENCODER.
5. 固定方式：止付螺絲固定式 / Fixed mode: Set screw type

### ◆ 型號表示 / Product NO:

**SMT-20 - Ø6 x Ø6**

型號 / Type

孔徑 / Inside dia