



氧化鋯陶瓷軸承 ZrO₂ Ceramic Bearing For Industry

產品特色 *Product Feature*

在腐蝕環境中比不鏽鋼軸承壽命更長
Excellent chemical resistance than stainless steel bearing.

不加潤滑油脂，避免無塵環境中污染
No grease contamination concern in clean room application.

良好的耐腐蝕特性，在大部份酸鹼和溶劑環境中都可使用
Good corrosion resistance at most acid & alkaline environment.

強力型PEEK保持器使用壽命更長久
Power type PEEK retainer to extend bearing life.

無磁性，絕緣
Non-magnetism, insulation.

應用場合 *Application*

半導體濕式設備..... Semiconductor wet equipment

LCD 濕式設備..... LCD wet equipment

食品機械設備..... Food equipment

電鍍設備..... Plating equipment

化工設備..... Chemical process equipment

使用注意事項 *Operation Note*

陶瓷軸承公差配合時，以間隙配合為宜
Recommend loose clearance for ceramic bearing installation fit.

軸承裝置時，請勿以榔頭敲打，避免破裂
Don't strike the bearing when installing the bearing to shaft or bearing house.

若使用環境有強酸，建議請先與我們討論使用狀況
Discuss for chemical compatibility when used on strong acid chemical environment.

CF Series

內外環	Rings	ZrO ₂ Ceramic
保持器	Retainer	PEEK Resin
滾珠	Ball	ZrO ₂ ; Si ₃ N ₄ Ball
產品料號	P/N	CF□□□□KZ

